

# RG-EW1800GX PRO 1800M Wi-Fi 6 Dual-band Gigabit Mesh Router


DATASHEET



### Highlights


- An Unprecedented Wireless Experience with Wi-Fi 6
- Strong Signal Received, Feels like "wall-less"
- Born For Multi-user, support up to 192 terminals
- Exclusive Reyee Mesh provides full space coverage Wi-Fi solution
- Take control of your home network at your fingertips

### Highlight Features






### Highlight Features





### Highlight Features





Basic Basic		
Dimensions ( W×D×H)	180 mm x 180 mm x 30 mm (7.09 in. × 7.09 in. × 1.18 in. antennas not included)	
Weight	0.55 kg (packages not included)	
Wi-Fi Standards	Wi-Fi 6 (802.11ax)	
MIMO	2.4 GHz, 2×2, MU-MIMO 5 GHz, 2×2, MU-MIMO	
Max. Wi-Fi Speed	2.4 GHz: 574 Mbps 5 GHz: 1201 Mbps	
Channel Width	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80 MHz	
Antennas	4	
Antennas Type	External Omnidirectional	
Antenna Gain	2.4 GHz: 5 dBi 5 GHz: 6 dBi	
WAN Port	1×10/100/1000 Base-T Port	
LAN Ports	4×10/100/1000 Base-T Ports	
Recommended Users	48	
Max. Users	192	
Power Supply	DC 12V/1.5A	
Power Consumption	≤18W	
Operation Frequency Bands	802.11b/g/n/ax: 2.400 GHz to 2.483 GHz 802.11a/n/ac/ax: 5.150 GHz to 5.350 GHz country-speci ic restrictions apply	
Transmit Power	Regular: CE EIRP: ≤20 dBm (2.4 GHz) ≤20 dBm (5 GHz)	
Operating Temperature	0 °C to +45 °C (32 °F to 113 °F)	
Operating Humidity	5% to 95% Noncondensing	
Certifications	CE,RoHS	

Wireless		
OFDMA	~	
MU-MIMO	<b>✓</b>	
BSS Coloring	<b>✓</b>	
Maximum Number of SSIDs	6	
SSID Hiding	<b>✓</b>	
Band Steering	<b>✓</b>	
Guest Wi-Fi	<b>✓</b>	
WPA/WPA2	<b>✓</b>	
WPA3	-	
Roaming	Layer 2 Roaming	
Blacklist	<b>✓</b>	
Reyee Mesh	<b>✓</b>	
Mesh Pairing by Hardware	<b>✓</b>	
Mesh Pairing by Mesh Button	<b>✓</b>	
Mesh Pairing by Eweb	<b>✓</b>	
Recommended Hop Count	≤5	
Wi-Fi Optimization	<b>✓</b>	
QoS (WMM)	<b>✓</b>	
WPS	-	
Transmission Power Adjustment	<b>✓</b>	
Hardware Control of the Control of t		
CPU	MT7621	
Flash	16M	



Hardware Control of the Control of t		
RAM/SDRAM	256M	
Color	White	
System LED Indicator	✓	
Reyee Mesh LED Indicator	~	
Reyee Mesh Button	✓	
Power Button	-	
Reset Button	<b>✓</b>	
DC Connector Dimensions	5.5 mm x 2.1 mm x 9.5 mm (0.22 in. × 0.08 in. × 0.37 in. antennas not included)	
	WAN	
Static IP	<b>✓</b>	
DHCP	<b>✓</b>	
PPPoE	<b>✓</b>	
Learning PPPoE Account & Password	<b>✓</b>	
VLAN Tagging	<b>✓</b>	
	LAN	
DHCP Server	~	
Client List	~	
Static IP Assignment	<b>✓</b>	
Port-Based Flow Control	~	
Features		
IPv6	~	
DDNS	~	
IPTV	<b>✓</b>	

	Features	
Alarm	~	
Diagnosis	<b>✓</b>	
UPnP	~	
ARP Binding	<b>✓</b>	
Port Mapping	<b>✓</b>	
DMZ Host	<b>✓</b>	
Rate Limitation of Terminals	<b>✓</b>	
Hardware Acceleration	<b>✓</b>	
MAC Address Cloning	<b>✓</b>	
Cloud Management	<b>✓</b>	
Repeater Mode	~	
WISP Mode	-	
	Security	
PPTP VPN Server	<b>✓</b>	
PPTP VPN Client	<b>✓</b>	
L2TP VPN Client	-	
Parental Control	<b>✓</b>	
Protect TCP Flood Attacks	<b>✓</b>	
Protect ICMP Attacks	<b>✓</b>	
Protect UDP Flood Attacks	<b>✓</b>	
System		
Default Access/Password	192.168.110.1 No Password Required by Default	
URL Access	<b>✓</b>	

System	
Local Upgrade	<b>✓</b>
Online Upgrade	<b>✓</b>
APP Upgrade	<b>✓</b>
Syslog	-
Backup	<b>✓</b>
Factory Reset	<b>✓</b>
Language	Chinese English Vietnamese Indonesian Thai Arabic Traditional Chinese Spanish Russian

### Package Contents

Model	RG-EW1800GX PRO
Wireless Router	1
Power Adapter	1
Quick Start Guide	1
Cat5e UTP Cable	1



Redefine your easy network



Ruijie Networks Co., Ltd Floor 11, East Wing, Zhongyipengao Plaza, No.29 Fuxing Road, Haidian District, Beijing China Website: https://www.ruijienetworks.com