Cat. 7 4x2x23/1 AWG S/FTP FR-LSZH
COMPUTER & LAN
P/N 9928001103

TELECOM

Applications

Indoor use, fixed installations, High data rates, Data processing and information systems, Telecom systems, Optimized for IEEE 802.3bt 4PPoE



Outer Jacket Material	Outer diameter	Weight
FR-LSZH	7.1 mm nom.	50 kg/km

General Construction

4 individually foil-shielded twisted pairs, cabled together with tinned copper drain conductor, overall braid-shielded and jacketed.
The cable conforms to IEC 61156-5 Cat. 7, Cat. 6_A Cat. 6, and Cat. 5e requirements and tested up to 1000 MHz.

Design & Materials

Conductor Material	Annealed Bare Copper
Conductor Size (AWG)	23
Conductor Construction	Solid
Insulation Material	Cellular PO
Insulation O.D. (mm nom)	1.38
Conductor Unit Identification	Solid/stripe
Color Code	Per TIA/EIA 568-B
Ind. Shield Material	Aluminum/Polyester Foil
Ind. Shield Design	100% Coverage
Conductor Unit Lay-Up	Pairs
Overall Braid Shield	Yes
Braid Coverage (% nom)	35
Overall Drain-wire Material	Annealed Tinned Copper
Overall Drain-wire size (mm)	0.41
Overall Drain-wire Construction	Solid
Total Number Of Conductors	8
Outer Jacket Color	Red
Other Jacket Colors Available	Yes

TELDOR
Cables & Systems Ltd.

Cat. 7 4x2x23/1 AWG S/FTP FR-LSZH
P/N 9928001103

TELECOM

Marking	Teldor Standard|Per request

Performance

Frequency Range (MHz)	1 - 1000
Impedance (Ω)	100
Transfer Impedance Grade	Grade 2
Coupling Attenuation	Type I
Max. DC Resistance (Ω/km@20°C)	73
Max. Resistance Unbalance (%)	2
Capacitance Unbalance (pF/m max)	1.2
Velocity of Propagation (% nom)	78
Propagation Delay Skew (ns/100m max)	25
Dielectric Strength (V/minute)	700
Dielectric Strength to Shield (V/minute)	700
Min. Insulation Resistance (GΩ•km)	5
Max. Installation Tensile Load (N max.)	100
Min. Bend Radius (mm)	60
Min. Operating Temperature (°C)	-40
Max. Operating Temperature (°C)	+65

Standards

Flammability Rating
IEC 60332-1
UL 1581 VW-1
EN 50575:2014 D_{ca}s2d2a2 (CPR)

Applicable Standards
IEC 61156
IEC 61156-5
IEEE 802.3af (PoE)
IEEE 802.3at (PoE+)
IEEE 802.3bt (4PPoE)
ISO/IEC 11801-1
ANSI/TIA-568.2-D
RoHS 3 2015/863/EU

Electrical Properties

Cat. 7 Horizontal Cables*

Freq. MHz	Attenuation dB/100m 20°C		PS NEXT Loss dB		NEXT Loss dB		RL dB		PS ANEXT dB		PS ELFEXT dB		ELFEXT dB	
	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7
1	2.0	2.0	105.0	75.0	108.0	78.0	22.0	20.0	68.0	N/A	95.0	75.0	98.0	78.0
4	3.6	3.7	98.0	75.0	101.0	78.0	25.0	23.0	68.0	N/A	90.0	75.0	93.0	78.0
10	5.6	5.8	95.0	75.0	98.0	78.0	28.0	25.0	68.0	N/A	86.0	71.0	89.0	74.0
20	7.9	8.3	90.0	75.0	93.0	78.0	28.0	25.0	68.0	N/A	80.0	65.0	83.0	68.0
30	9.7	10.2	85.0	75.0	88.0	78.0	27.0	23.8	68.0	N/A	76.0	61.5	79.0	64.5
100	18.0	19.0	80.0	69.4	83.0	72.4	24.0	21.1	68.0	N/A	66.0	51.0	69.0	54.0
150	22.4	23.6	78.0	66.7	81.0	69.7	22.0	18.8	65.0	N/A	63.0	47.5	66.0	50.5
200	26.0	27.5	78.0	65.0	81.0	68.0	21.0	18.0	65.0	N/A	60.0	45.0	63.0	48.0
250	29.4	31.0	75.0	63.4	78.0	66.4	20.0	17.3	62.0	N/A	58.0	43.0	61.0	46.0
300	32.5	34.2	75.0	62.2	78.0	65.2	19.0	17.3	62.0	N/A	52.0	41.5	55.0	44.5
400	38.0	40.0	70.0	60.4	73.0	63.4	19.0	17.3	62.0	N/A	49.0	38.9	52.0	41.9

500	43.0	45.2	70.0	58.9	73.0	61.9	19.0	17.3	62.0	N/A	47.0	37.0	50.0	40.0
600	47.6	50.1	70.0	57.7	73.0	60.7	19.0	17.3	62.0	N/A	45.0	35.4	48.0	38.4

*Supplied cables meet the minimum Cat. 7 transmission requirements as per IEC 61156-5 Ed. 2

Teldor Cables & Systems Ltd. (“Teldor”) reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Version 1.6 | Last update: 2024-05-09