

Cat. 7_A 4x2x23/1 AWG S/FTP FR-LSZH IEC60332-3

COMPUTER & LAN

P/N 99XG504122

TELECOM

Applications

Data-Centers/SANs, Indoor use, fixed installations, High bandwidth digital applications with low BER, High data rates, Telecom systems, Optimized for IEEE 802.3bt 4PPoE, Compliance with low voltage safety earth-connection and grounding regulations




Outer Jacket Material
FR-LSZH



Outer diameter
8.1 mm nom.



Weight
66 kg/km



General Construction

The cable contains 4 individually aluminum-foil screened twisted pairs cabled with a drain conductor and overall braid-shielded to an S/FTP form and an overall jacket.

Design & Materials

Conductor Material	Annealed Bare Copper
Conductor Size (AWG)	23
Conductor Construction	Solid
Insulation Material	SFS PO
Insulation O.D. (mm nom)	1.38
Conductor Unit Identification	Solid/stripe
Color Code	Per TIA/EIA 568-B
Ind. Shield Material	Aluminum/Polyester Foil
Ind. Shield Design	Helically applied aluminum foil, 100% coverage
Conductor Unit Lay-Up	Pairs
Overall Shield Design	Braid
Overall Shield Material	Tinned-copper braid
Overall Braid Shield	Yes
Overall Braid Material	Annealed Tinned Copper
Braid Coverage (% nom)	55
Overall Drain-wire Material	Annealed Tinned Copper
Overall Drain-wire size (mm)	0.41
Overall Drain-wire Construction	Solid
Total Number Of Conductors	8

Cat. 7_A 4x2x23/1 AWG S/FTP FR-LSZH IEC60332-3 P/N 99XG504122

TELECOM

Outer Jacket Color	Light Gray
Other Jacket Colors Available	Yes
Marking	Teldor Standard Per request

Performance

Frequency Range (MHz)	1 - 1500
Impedance (Ω)	100
Transfer Impedance Grade	Grade 1
Coupling Attenuation	Type I
Max. DC Resistance (Ω/km@20°C)	73
Max. Resistance Unbalance (%)	2
Capacitance (pF/m)	44
Capacitance Unbalance (pF/m max)	1.2
Velocity of Propagation (% nom)	78
Propagation Delay Skew (ns/100m max)	20
Dielectric Strength (V/minute)	700
Dielectric Strength to Shield (V/minute)	700
Min. Insulation Resistance (GΩ•km)	5
Max. Installation Tensile Load (N max.)	130
Min. Bend Radius (mm)	70
Min. Operating Temperature (°C)	-40
Max. Operating Temperature (°C)	+70
UV Resistance	Yes

Standards

Flammability Rating
 IEC 60332-1
 IEC 60332-3
 UL 1581 VW-1

Applicable Standards
 IEC 61156
 IEC 61156-5
 IEEE 802.3af (PoE)
 IEEE 802.3at (PoE+)
 IEEE 802.3an 10GBASE-T 10 Gigabit Ethernet
 IEEE 802.3bt (4PPoE)
 ISO/IEC 11801-1
 ANSI/TIA-568-C.2
 RoHS 3 2015/863/EU



Electrical Properties

IEC 33

Cat. 7_A Horizontal Cables*

Freq. MHz	Attenuation dB/100m 20°C		NEXT Loss dB		PS-NEXT Loss dB		RL dB		PS ANEXT dB		PS ELFEXT dB		ELFEXT dB	
	Typical Value	Cat. 7 _A	Typical Value	Cat. 7 _A	Typical Value	Cat. 7 _A	Typical Value	Cat. 7 _A	Typical Value	Cat. 7 _A	Typical Value	Cat. 7 _A	Typical Value	Cat. 7 _A
1	1.8	2.0	103.0	78.0	100.0	75.0	31.0	20.0	100.0	67.0	108.0	75.0	110.0	78.0
4	3.2	3.8	103.0	78.0	100.0	75.0	31.0	23.0	100.0	67.0	105.0	75.0	108.0	78.0
10	4.9	5.8	103.0	78.0	100.0	75.0	31.0	25.0	100.0	67.0	100.0	71.0	103.0	74.0
20	7.0	8.2	103.0	78.0	100.0	75.0	31.0	25.0	100.0	67.0	90.0	65.0	93.0	68.0
30	8.6	10.1	103.0	78.0	100.0	75.0	31.0	23.8	100.0	67.0	90.0	61.5	93.0	64.5

Cat. 7_A 4x2x23/1 AWG S/FTP FR-LSZH IEC60332-3
P/N 99XG504122

TELECOM

100	15.7	18.5	103.0	78.0	100.0	75.0	31.0	21.1	100.0	62.5	85.0	51.0	88.0	54.0
150	19.4	22.8	103.0	78.0	100.0	75.0	26.0	18.8	95.0	59.8	84.0	47.5	87.0	50.5
200	22.5	26.5	98.0	76.8	95.0	73.8	26.0	18.0	95.0	58.0	80.0	45.0	83.0	48.0
250	25.3	29.7	96.0	75.4	93.0	72.4	25.0	17.3	92.0	56.5	78.0	43.0	81.0	46.0
300	27.8	32.7	95.0	74.2	92.0	71.2	25.0	17.3	92.0	55.3	75.0	41.5	78.0	44.5
400	32.3	38.0	94.0	72.3	91.0	69.3	23.0	17.3	92.0	53.4	70.0	38.9	73.0	41.9
500	36.3	42.7	93.0	70.9	90.0	67.9	23.0	17.3	90.0	52.0	69.0	37.0	72.0	40.0
600	40.0	47.1	92.0	69.7	89.0	66.7	23.0	17.3	90.0	50.8	68.0	35.4	71.0	38.4
1000	52.7	62.0	88.0	66.4	85.0	63.4	21.0	17.3	90.0	47.5	67.0	31.0	70.0	34.0

*Supplied cables meet the minimum Cat. 7_A transmission requirements as per IEC 61156-5

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Version 1.6 | Last update: 2024-06-05